


SE 2600 Series

CNC Turning Center for Productivity

WIA Machine Tools CNC Turning Center

WIA MACHINE TOOLS



Technical Leader

The CNC Turning Center SE2600 Series, designed with WIA Machine Tools's engineering expertise to maximize productivity by enhancing rigidity and accuracy of machining.

ITEM	Main Spindle	Sub Spindle	Bed Type		Turret		Y-Axis
	10"	6"	Std. Bed	Long Bed	Standard	Mill turret	
SE2600	●		●		●		
SE2600L	●			●	●		
SE2600M	●		●			●	
SE2600LM	●			●		●	
SE2600Y	●		●			●	●
SE2600LY	●			●		●	●
SE2600SY	●	●	●			●	●
SE2600LSY	●	●		●		●	●

SE 2600 Series

High-speed Type CNC Turning Center for Productivity

- 30° slanted one-piece bed structure with high rigidity
- Applying high-rigidity roller type LM guideway on all axis
- Hydraulic NC tailstock with position control (SE2600/M/Y)
- Multi-tasking operation with wedge type Y-axis structure (SE2600Y/SY/LY/LSY)
- Improved user convenience by applying the latest controller of FANUC





APPLICATIONS & PARTS

Reduced machining time by multi-tasking operation

SE2600Y Series with Y-axis makes it possible to work high-valued product with integrated processing using sub spindle and various rotary tools in short time.



WHEEL HUB




DRIVE GEAR



WORM SHAFT


MACHINING CAPABILITY

WIA Machine Tools is doing its best to get the world-top class quality, productivity and technology for meeting the global customers' needs through its full R&D investment.




End Mill
(Material : SM45C)

Tool Dia.	Ø16 mm (Ø0.6")
Spindle rpm	995 r/min
Forwarding speed	150 mm/min
Cutting speed	50 m/min
Machining depth	16 mm (0.6")




Drill
(Material : SM45C)

Tool Dia.	Ø14 mm (Ø0.6")
Spindle rpm	1,820 r/min
Forwarding speed	300 mm/min
Cutting speed	80 m/min




O.D Turning
(Material : SM45C)

Machining Dia.	Ø92 mm (Ø3.5")
Machining depth	4 mm (0.16")
Spindle rpm	727 r/min
Cutting speed	210 m/min
Forwarding speed	0.55 mm/rev
Chip discharging amount	462 cc/min



U-Drill
(Material : SM45C)

Tool Dia.	Ø60 mm (Ø2.4")
Spindle rpm	551 r/min
Forwarding speed	0.33 mm/rev
Cutting speed	104 m/min
Chip discharging amount	512 cc/min



Tap
(Material : SM45C)

Tap spec.xPitch	M14×P2.0
Spindle rpm	133 r/min
Forwarding speed	2 mm/min
Cutting speed	5 m/min

※ The above result might be different by types of processing circumstances.

01 SE2600/M/L/LM

The Best Productivity 10" CNC Turning Center

Turret


- Std. Turret : 10 EA [Opt. 12 EA]
- Mill Turret : BMT55 12 EA [Opt. 24 EA]

Tail Stock

- MT#4
- Hydraulic NC Tailstock

Spindle

- Std. : 3,500 r/min
- Opt. : Power Up 2,500 r/min
- C-Axis Control : 0.001°



Automatic Grease Supply Unit

Automatic grease lubrication system, which does not require frequent refill, is applied as standard to improve user convenience and cost efficiency. (SE2600L/LM/LY : Oil lubrication)

REDUCTION OF NON-CUTTING TIME BY FAST RAPID SPEED

30° SLANTED ONE-PIECE BED

Optimal Structural Analysis

Structural analysis was applied to the design of the machine to increase the tool post body and reduce the machine's height so as to maintain the bed's dynamic rigidity even during high-speed machining.




Bed Slant **30°**

ENHANCED VIBRATION ABSORPTION THANKS TO INCREASED GROUND AREA

GUIDEWAY

High-Speed Roller LM Guideway

Linear roller guideways are applied to reduce non-cutting time and bring high rigidity.



RIGIDITY HAS INCREASED 30% COMPARED TO THE BALL BEARING LM GUIDE

Rapid Traverse Rate
(X/Z)

30/30 m/min (1,181/1,181 ipm)

Ball Screw

Travel is stabilized by fastening both ends of the ball screw using the double anchored method. In particular, a large diameter ball screw with proper preload reinforces sturdiness and resistance to thermal displacement.

Travel (X/Z)

SE2600

265/680 mm (10.4"/26.8")

SE2600L

265/1,100 mm (10.4"/43.3")

SE2600M

255/680 mm (10"/26.8")

SE2600LM

255/1,100 mm (10"/43.3")

02 SE2600Y/SY/LY/LSY

Y-axis Structure Design for Machining High Value-added Complex Workpiece

BMT55 Mill Turret

- Speed : 6,000 r/min
- Max. Power : 5.5 kW
- Max. Torque : 52.5 N.m

Sub Spindle (SE2600SY)

- Chuck Size : 6"
- Speed : 4,500r/min

Spindle

- Std. : 3,500 rpm
- Opt. : Power Up 2,500 r/min



Travel (X/Y/Z/ZB)

SE2600Y/SY

255/110/680/660 mm

(10"/4.3"/26.8"/26")

SE2600LY/LSY

255/110/1,100/1,080 mm



(10"/4.3"/43.3"/42.5")

REALIZATION OF COMPLEX MACHINING THROUGH Y-AXIS & SUB-SPINDLE


COMPLEX MACHINING

Y-Axis Structure


SE2600Y/LY/SY/LSY with Y-axis added can even machine products that cannot be machined on the 2-axis turning centers. Contributes to productivity improvement with machining being performed on a single machine without a separate machining center.




Keyway Milling




Multi-sided machining



Eccentric hole machining



X+Y axis circular interpolation




Fine Grooving



Sub Spindle (SE2600SY/LSY)

When the main spindle cutting is completed, the sub spindle rotation is synchronized with the main spindle allowing the workpiece to be transferred to the sub spindle, and machining can begin on the back side of the workpiece.



30° SLANTED ONE-PIECE BED


By designing the machine bed at 30°, stability has been improved by reducing the height of the machine which previously used a 45° inclined Y-axis CNC turning center.




Bed Slant **30°**

- Height of the machine with the previous 45° inclined Y-axis turning center : 2,225 mm (87.6")
- SE2600SY machine height : 1,960 mm (77.2") - 12% height reduction

Previous model



SE2600SY



03 HIGH PRECISION SPINDLE

High-performance Spindle for Powerful Cutting and Precision

Spindle Specifications

[] : Option

Model	Spindle Speed	Motor (Max./Cont.)	Torque (Max./Cont.)
SE2600/M/L/LM SE2600Y/LY	3,500 rpm	18.5/15 kW (25/20 HP)	470.9/286.4 N·m (347.3/211.2 lbf·ft)
	[2,500 rpm]	[26/18.5 kW (35/25 HP)]	[734/522 N·m (541.4/385 lbf·ft)]
SE2600SY/LSY	Main : 3,500 rpm	18.5/15 kW (25/20 HP)	470.9/286.4 N·m (347.3/211.2 lbf·ft)
	Main : [2,500 rpm]	[26/18.5 kW (35/25 HP)]	[734/522 N·m (541.4/385 lbf·ft)]
	Sub : 4,500 rpm	7.5/5.5 kW (10/7.5 HP)	85/47 N·m (62.7/34.7 lbf·ft)



HEAVY DUTY CUTTING & HIGH ACCURACY

MAIN SPINDLE


Spindle for Heavy Duty Cutting

The main spindle is designed with the same structure as that often found in larger sized machines. The combination of double cylindrical roller bearings and angular contact ball bearings leads to excellent heavy duty cutting performance. Also, machining performance is enhanced by applying **ribstar belt** to minimize noise and belt slipping problems.

The spindle is designed with a labyrinth structure to minimize possible bearing damage from coolant and to improve machining stability.

C-axis Control for All Models

The SE2600 Series 'M/Y' Type (featuring a mill turret) can control the C-axis by 0.001°, and the SE2600 (featuring a turning turret) can control the C-axis by 0.03°.



Model	Chuck Size	Max. Turning Length	Max. Turning Dia.	Bar Capacity
SE2600	10 inch	671 mm (26.4")	Ø460 mm (18.1")	Ø81 mm (3.1")
SE2600M		630 mm (24.8")	Ø380 mm (15")	
SE2600Y/SY		653 mm (25.7")		
SE2600L		1,091 mm (43")	Ø460 mm (18.1")	
SE2600LM		1,050 mm (41.3")	Ø380 mm (15")	
SE2600LY/LSY		1,073 mm (42.2")		

6 INCH SUB SPINDLE (SE2600SY/LSY)

By applying a high-performance sub-spindles with the maximum output of 7.5kW (10HP) and the maximum torque of 85N.m, powerful cutting performance can be demonstrated even in the secondary process using the sub-spindles.



04 SERVO TURRET

Excellent Splitting Accuracy, Strong Tool Clamping

Standard Turret (SE2600/L)

[] : Option

No. of Tools

10 [12]_{EA}

Tool Size (O.D/I.D)

□25/Ø50 mm (□1"/Ø2")

Indexing Time

0.15_{sec}

Mill Turret (SE2600M/LM/Y/LY/SY/LSY)

Type	Speed	Motor (Max./Cont)	Torque (Max./Cont)	Collet Size
BMT55	6,000 rpm	5.5/3.7 kW (7.4/5 HP)	52.5/26.5 N·m (38.7/19.5 lbf·ft)	ER25 (Ø16)

Standard : 12-angle 12P (30° rotation) → Optional : 12-angle 24P (15° rotation)

Expanded machining area by increasing the number of tools attached (up to 24 tools)

VARIOUS DRIVEN PRECISION BMT TOOL HOLDERS

SERVO TURRET




Standard Turret (SE2600/L)

The standard turret is applied with high performance AC servo motor, improving machining reliability. 3-piece coupling shows excellent performance in indexing. Powerful hydraulic tool clamping minimizes tool tip deviation caused by load.

70Bar High Pressure Coolant **OPTION**

Turret is designed to utilize 70bar high pressure coolant and it shows optimum performance in machining difficult-to-cut material.



MILL TURRET

BMT55 Turret (SE2600M/LM/Y/LY/SY/LSY)

The BMT turret secures the tool with four bolts and key on the tool mounting surface of the turret, making it possible to powerfully fix the tool, ensuring high reliability in rigidity and precision.



Triple I.D Holder



Double O.D Holder



OPTION

12 Station 24 Position Turret

Efficient tooling is possible by adjusting the partition angle of the turret, which allows a maximum of two external tools per side and three internal tools per side.

ITEM		STd. 12 Station 12 Position	Opt. 12 Station 24 Position
Turret Angle of Rotation		30°	15°
I.D Holder	Single	Ø40 (Ø1 1/2")	Ø40 (Ø1 1/2")
	Double	Ø20 (Ø3/4")	-
	Triple	-	Ø20 (Ø3/4")
O.D Holder	Single	□25 (□1")	□20 (□3/4")
	Double	-	□20 (□3/4")

※ 24P applicable exclusive to the mill turret

05 USER CONVENIENCE

Various Devices for User Friendly

HYDRAULIC NC TAILSTOCK


Optimal tail stock line-up for each machine's characteristic

SE2600 series consist of optimized tail stock line-up considering machine's characteristic.

SE2600/M/Y with a standard bed adopts a hydraulic NC tailstock as standard to improve user convenience.


Also, SE2600L/LM/LY with a long bed adopts a hydraulic quill-type tailstock as standard for strong support of long workpiece.

SE2600/M/Y
Hydraulic NC Tailstock



- > Structure in which the tailstock moves independently from the turret (Position control : 0.1mm)
- > Stabilization of tailstock body hydraulic pressure
- > Turret moves independently while the tailstock moves to reduce machining setup time
- > MT#4 live center standard application

SE2600L/LM/LY
Hydraulic Quill Tailstock




- > A structure that moves by fixing the tailstock to the saddle
- > After fixing the tailstock, the quill operated by hydraulic pressure advances to stabilize the material
- > High rigidity tail spindle and enhancement in thrust
- > Suitable for workpieces subject to vibration during machining and heavy machining load



HW-TMS (TAILSTOCK OPERATION)

This software is capable of manipulation and data management of tailstock operations through intuitive GUI.



CHIP DISPOSAL SOLUTION

Separation Type Coolant Tank

The user convenience has been significantly improved by the separation type coolant tank without having to separate the chip conveyor .



Hinge	Chip Type : Roughing Chip, Long Chip, Chip complex	Material : SS41, 45C, Cast Steel	Front-Right Direction
	Highly efficient when disposing a lot of chips. Capable of handling stringy chips..		
Scraper	Chip Type : Finely broken chip blown out	Material : cast Iron, Nonferrous	
	Convenient for shortly cut chips.		
※ Drum Filter	Chip Type : Powder, Micro Chip	Material : AL	
	Advantageous in precision, as the chips do not flow in to the coolant nozzle.		

※ When ordering a drum filter chip conveyor, prior consult with hyudai wia's sales person.

HIGH PRECISION SYSTEM & COOLANT UNIT **OPTION**



Q-Setter (Automatic/Manual)



Linear Scale



Gun Coolant



High Pressure Coolant



Chuck Coolant (Upper Chuck)



Chuck Air Blow (Upper Chuck)

06 FANUC - Smart Plus

The Compatible All-round Control




15" Touch-type Monitor as a standard

Fast Cycle Time Technology	
Smart Machine Control	Fine Surface Technology
	Smart Servo Control Technology
Conversational Program	SmartGuide-i
i-HMI	Machining-aid Function
Part Program Storage	5120M (2MB)
No. of Registerable Programs	1000 EA

Servo Learning Oscillation Function for Chip Breaking **OPTION**

- **Machining Method** : The tool cuts the workpiece moving in a zigzag pattern. (Oscillating) → Air cut section occurs → Long chips break
- **Advantage** : Increase tool life, Enhance surface finishing, Improve chip disposal
- **Machine** : All turning centers with FANUC controller (Option)



(Developed special screen page for servo learning oscillation function / Even when this function is applied, the cycle time remains same.)

8Ch. Thermal displacement compensation **OPTION**



Control Software

Thermal Sensor

Spindle thermal displacement error correction

Thermal Sensor

Structure thermal displacement error correction

Machine tools generate thermal displacement due to heat during machining.

WIA MACHINE TOOLS detect thermal changes through thermal sensors installed on the main thermal sources of the machine.

In addition, a thermal displacement compensation device that predicts the amount of thermal displacement according to the amount of thermal change and provides a command to the motor with a compensated value to maintain consistent precision is provided as an option.

SMART CNC (FANUC Smart Plus)



1. Dialogue Program (Smart Guide-i)

This software offers the maximum user convenience through dialogue manipulation from setup to processing. This includes writing processing programs and simulation checks.

2. LAUNCHER

This software offers shortcuts for quick access to specialized features and frequently used features.

SPECIFICATIONS

Standard & Optional

Spindle		SE2600/L	SE2600M/LM
Main Sp. Hollow Chuck 3 Jaw	10"	●	●
	12"	○	○
Main Sp. Solid Chuck 3 Jaw	10"	○	○
	12"	-	-
Standard Soft Jaw (1set)		●	●
Chuck Clamp Foot Switch		●	●
2 Steps Hyd. Pressure Device		○	○
Spindle Inside Stopper		☆	☆
Cs-Axis		● (0.03")	● (0.001")
Chuck Open/Close Confirmation Device		●	●
2 Steps Chuck Foot Switch		○	○
Turret			
Tool Holder		●	●
Mill Turret	BMT55	-	●
	12 Station 12P	-	●
	12 Station 24P	-	○
Straight Milling Head	Collet Type, 2ea	-	●
Angular Milling Head	Collet Type, 2ea	-	●
Straight Milling Head	Adapter Type	-	○
Angular Milling Head	Adapter Type	-	○
Boring Sleeve		●	●
Drill Socket		○	○
U-Drill Holder		●	●
U-Drill CAP		●	●
Angle Head		-	☆
Tail Stock & Steady Rest			
Hydraulic NC Tail Stock (Std. Live Center)		●/-	●/-
Quill Type Tail Stock	Manual	○/●	○/●
	Programmable	○	○
	MT4 Live	○/●	○/●
	MT5 Live	○	○
	MT4 Built-in	○	○
High Precision Live Center		☆	☆
2 Steps Tail Stock Pressure System		-	-
Quill Forward/Reverse Confirmation Device		○	○
Tail Stock Foot Switch		○	○
Coolant & Air Blow			
Standard Coolant (Nozzle)		●	●
Chuck Coolant (Upper Chuck)		○	○
Gun Coolant		○	○
Through Spindle Coolant (Only for Special Chuck)		☆	☆
Chuck Air Blow (Upper Chuck)		-	-
Sub Chuck Air Blow		○	○
Turnmill Through Coolant		-	○
Tail Stock Air Blow (Upper Tail Stock)		○	○
Turret Air Blow		☆	☆
Air Gun		○	○
Through Spindle Air Blow (Only for Special Chuck)		-	-
High Pressure Coolant	0.5Bar	●	●
	6Bar	○	○
	20Bar	○	○
	70Bar	○	○
		○	○
Power Coolant System (For Automation)		☆	☆
Coolant Chiller (When selecting Sub Tank Type, Chip Conveyor)		-	-
Chip Disposal			
Coolant Tank	Front(200 ℓ [52.8 gal])	●/-	●/-
	Front(230 ℓ [60.8 gal])	-/●	-/●
	Front(170 ℓ [44.9 gal])	○	○
		○	○
Chip Conveyor (Hinge/Scraper)	Front (Right)	○	○
	Rear (Rear)	○	○
Special Chip Conveyor (Drum Filter)		-	-
Chip Wagon	Standard (180 ℓ [47.5 gal])	○	○
	Swing (200 ℓ [52.8 gal])	○	○
	Large Size (330 ℓ [87.2 gal])	○	○
	Customized	☆	☆

● : Standard ○ : Option ☆ : Prior Consultation - : Non Applicable

Electric Device		SE2600/L	SE2600M/LM
Call Light	1Color : ●	●	●
Call Light & Buzzer	3Color : ●●● B	○	○
Electric Cabinet Light		○	○
Remote MPG		○	○
Work Counter	Digital	○	○
Total Counter	Digital	○	○
Tool Counter	Digital	○	○
Multi Tool Counter	6ea	○	○
	9ea	○	○
Electric Circuit Breaker		○	○
AVR (Auto Voltage Regulator)		☆	☆
Transformer	25kVA	○	○
Measurement		○	○
Q-Setter		○	○
Automatic Q-Setter		○	○
Work Close Confirmation Device (Only for Special Chuck)	TACO	○	○
	SMC	○	○
Work Setter		☆	☆
Linear Scale	X axis	○	○
	Z axis	○	○
Coolant Level Sensor (Only for Chip Conveyor)		☆	☆
Environment			
Air Conditioner		○	○
Dehumidifier		○	○
Oil Mist Collector		☆	☆
Oil Skimmer (Only for Chip Conveyor)		○	○
MQL (Minimal Quantity Lubrication)		☆	☆
Fixture & Automation			
Auto Door	High-speed	○	○
Auto Shutter (Only for Automatic System)		○	○
Sub Operation Pannel		☆	☆
Bar Feeder Interface		○	○
Bar Feeder		☆	☆
Extra M-Code 4ea		○	○
Automation Interface		☆	☆
I/O Extension (IN & OUT)	16 Contact	○	○
	32 Contact	○	○
Parts Catcher		○	○
Turret Work Pusher (For Automation)		☆	☆
Parts Conveyor (Required Main Parts Catcher)		○	○
Semi Automation System		☆	☆
Hyd. Device			
Standard Hyd. Cylinder	Hollow	●	●
Standard Hyd. Unit	35bar/20 ℓ (5.3gal)	●	●
S/W			
Dialogue Program (HW-DPRO)		○	○
DNC software (HW-eDNC)		○	○
SmartGuide-i : FANUC		●	●
Smart S/W		☆	☆
Safety Device			
Front Door Interlock		●	●
Total Splash Guard		●	●
Back Spin Torque Limiter (BST)		●	●
Chuck Hydraulic Pressure Maintenance Interlock		☆	☆
ETC			
Tool Box		●	●
Customized Color	Need Munsel No.	☆	☆
CAD & CAM		☆	☆
Thermal displacement compensation		○	○

※ Thermal Displacement Compensation device is recommended, when more than 6 bar of high pressure coolant is applied, for the high quality machining.
Specifications are subject to change without notice for improvement.

SPECIFICATIONS

Standard & Optional

● : Standard ○ : Option ☆ : Prior Consultation - : Non Applicable

Spindle		SE2600Y/LY	SE2600SY/LSY
Main Sp. Hollow Chuck 3 Jaw	10"	●	●
Main Sp. Solid Chuck 3 Jaw	10"	○	○
Sub Sp. Hollow Chuck 3 Jaw	6"	-	●
Sub Sp. Solid Chuck 3 Jaw	6"	-	○
Standard Soft Jaw (1set)		●	●
Chuck Clamp Foot Switch		●	●
2 Steps Hyd. Pressure Device		○	○
Spindle Inside Stopper		☆	☆
Cs-Axis (0.001")	Main	●	●
	Sub	-	●
Chuck Open/Close Confirmation Device		●	●
2 Steps Chuck Foot Switch		○	○
Sub Sp. Foot Switch		-	●
Turret			
Tool Holder		●	●
Mill Turret	BMT55	●	●
	12 Station 12P	●	●
	12 Station 24P	○	○
Straight Milling Head	Collet Type, 2ea	●	●
Angular Milling Head	Collet Type, 2ea	●	●
Straight Milling Head	Adapter Type	○	○
Angular Milling Head	Adapter Type	○	○
Boring Sleeve		●	●
Drill Socket		○	○
U-Drill Holder		●	●
U-Drill CAP		●	●
Angle Head		☆	☆
Adapter Set		○	○
Tail Stock & Steady Rest			
Hydraulic NC Tail Stock (Std. Live Center)		●/-	-
Quill Type Tail Stock	Manual	○/●	-
	Programmable	○	-
	MT4 Live	○/●	-
	MT5 Live	○	-
	MT4 Built-in	○	-
High Precision Live Center		☆	-
2 Steps Tail Stock Pressure System		-	-
Quill Forward/Reverse Confirmation Device		○	-
Tail Stock Foot Switch		○	-
Coolant & Air Blow			
Standard Coolant (Nozzle)		●	●
Chuck Coolant (Upper Chuck)		○	○
Gun Coolant		○	○
Through Spindle Coolant (Only for Special Chuck)		☆	☆
Bed Flushing (Only for Rear Coolant Tank)		○	○
Turnmill Through Coolant		○	○
Chuck Air Blow (Upper Chuck)		○	○
Sub Chuck Air Blow		-	○
Tail Stock Air Blow (Upper Tail Stock)		○	-
Turret Air Blow		☆	☆
Air Gun		○	○
Through Spindle Air Blow (Only for Special Chuck)		-	-
High Pressure Coolant	0.5Bar	●	●
	6Bar	○	○
	20Bar	○	○
	70Bar	○	○
Power Coolant System (For Automation)		☆	☆
Coolant Chiller (When selecting Sub Tank Type, Chip Conveyor)		-	-
Chip Disposal			
Coolant Tank	Front(200 ℔ [52.8 gal])	●/-	●/-
	Front(230 ℔ [60.8 gal])	-/●	-/●
	Front(170 ℔ [44.9 gal])	○	○
Chip Conveyor (Hinge/Scraper)	Front (Right)	○	○
	Rear (Rear)	○	○
Special Chip Conveyor (Drum Filter)		-	-
Chip Wagon	Standard (180 ℔ [47.5 gal])	○	○
	Swing (200 ℔ [52.8 gal])	○	○
	Large Size (330 ℔ [87.2 gal])	○	○
	Customized	☆	☆


Electric Device		SE2600Y/LY	SE2600SY/LSY
Call Light	1Color : ■	●	●
Call Light & Buzzer	3Color : ■ ■ ■ B	○	○
Electric Cabinet Light		○	○
Remote MPG		○	○
Work Counter	Digital	○	○
Total Counter	Digital	○	○
Tool Counter	Digital	○	○
Multi Tool Counter	6ea	○	○
	9ea	○	○
Electric Circuit Breaker		○	○
AVR (Auto Voltage Regulator)		☆	☆
Transformer	30kVA	○	○
Measurement		○	○
Q-Setter		○	○
Automatic Q-Setter		○	○
Work Close Confirmation Device (Only for Special Chuck)	TACO	○	○
	SMC	○	○
Work Setter		☆	☆
Linear Scale	X/Y/Z axis	○	○
Coolant Level Sensor (Only for Chip Conveyor)		☆	☆
Environment			
Air Conditioner		○	○
Dehumidifier		○	○
Oil Mist Collector		☆	☆
Oil Skimmer (Only for Chip Conveyor)		○	○
MQL (Minimal Quantity Lubrication)		☆	☆
Fixture & Automation			
Auto Door	High-speed	○	○
Auto Shutter (Only for Automatic System)		○/☆	○/☆
Sub Operation Panel		☆	☆
Bar Feeder Interface		○	○
Bar Feeder		☆	☆
Sub Sp. Work Pusher (Spring Type)		-	○/-
Sub Sp. Work Ejector (Pneumatic Type)		-	○/-
Extra M-Code 4ea		○	○
Automation Interface		☆	☆
I/O Extension (IN & OUT)	16 Contact	○	○
	32 Contact	○	○
Parts Catcher	Main	○	○
	Sub	-	○/-
Turret Work Pusher (For Automation)		☆	☆
Parts Conveyor (Required Main Parts Catcher)		○	○
Semi Automation System		☆	☆
Hyd. Device			
Standard Hyd. Cylinder	Hollow	●	●
Standard Hyd. Unit	35bar/20 ℔ (5.3gal)	●	●
S/W			
Dialogue Program (HW-DPRO)		○	○
DNC software (HW-eDNC)		○	○
SmartGuide-i : FANUC		●	●
Smart S/W		☆	☆
Safety Device			
Front Door Interlock		●	●
Total Splash Guard		●	●
Back Spin Torque Limiter (BST)		●	●
Chuck Hydraulic Pressure Maintenance Interlock		☆	☆
ETC			
Tool Box		●	●
Customized Color	Need Munsel No.	☆	☆
CAD & CAM		☆	☆
Thermal displacement compensation		○	○

※ Thermal Displacement Compensation device is recommended, when more than 6 bar of high pressure coolant is applied, for the high quality machining.
Specifications are subject to change without notice for improvement.


SPECIFICATIONS

Spindle Output/Torque Diagram


Main 3,500 rpm




Main 2,500 rpm - Power Up



SE2600SY/LSY : Sub 4,500 rpm




Mill Turret 6,000 rpm



SPECIFICATIONS

External Dimensions (SE2600 | SE2600M)


unit : mm(in)



SPECIFICATIONS

External Dimensions (SE2600L | SE2600LM)


unit : mm(in)



SPECIFICATIONS

External Dimensions (SE2600Y | SE2600YS)


unit : mm(in)



SPECIFICATIONS

External Dimensions (SE2600LY | SE2600LSY)

unit : mm(in)



SE2600 Series
CNC Turning Center

unit : mm(in)

Technical drawing of a circular machine component, likely a rotary table or indexing head, showing dimensions in inches (") and millimeters (mm) in parentheses.

Overall Dimensions:

- Overall Diameter: $\varnothing 562$ (14281)
- Overall Width: 470 (1185)

Internal Features and Dimensions:

- Central Circular Feature: $\varnothing 240$ (609.6)
- Inner Ring Dimensions:
 - Inner Diameter: $\varnothing 236$ (59.9)
 - Inner Ring Width: 35 (8.9)
- Outer Ring Dimensions:
 - Outer Diameter: $\varnothing 500$ (12700)
 - Outer Ring Width: 52 (1320)
- Radial Features:
 - Radial Distance from Center to Feature: 200 (7.9)
 - Radial Distance from Center to Feature: 200 (7.9)
 - Radial Distance from Center to Feature: 235 (9.3)
 - Radial Distance from Center to Feature: 265 (10.4) X-St.
- Angular Features:
 - Angular Distance: 40 (1.6)
 - Angular Distance: 30 (1.2)
 - Angular Distance: 37 (1.5)
- Max Turning Dia. (Maximum Turning Diameter): $\varnothing 460$ (11681)
- Max Turning Dia. (Maximum Turning Diameter): $\varnothing 254$ (6451)



[illegible]

unit : mm(in)

Technical drawing of a circular machine component, likely a manifold or flange, showing dimensions in millimeters (mm) and inches (in). The drawing includes a central circular face with 10 numbered ports (1-10) and 10 external ports (1-10) arranged radially. The central face has a diameter of $\varnothing 603$ (23.7) - Max Swing Dia. The external ports have various diameters and lengths. Key dimensions include:

- Overall diameter: 470 (18.5)
- Port diameters: $\varnothing 240$ (9.4), $\varnothing 260$ (10.2), $\varnothing 200$ (7.9), $\varnothing 250$ (9.8), $\varnothing 275$ (10.8), $\varnothing 215$ (8.5), $\varnothing 40$ (1.6), $\varnothing 16$ (0.6), $\varnothing 20$ (0.8).
- Port lengths: 165 (6.5), 80 (3.1), 35 (1.4), 190 (7.5), 65 (2.6), 118.1 (4.6), 101.9 (4), 126.5 (5), 85 (3.3), 58 (2.3), 61 (2.4).
- Other dimensions: 280 (11), 255 (10) - X-St., $\varnothing 380$ (15) Max - Turning Dia., $\varnothing 254$ (10").


Straight Milling Y-St.



SPECIFICATIONS

Tooling System (SE2600/L)

unit : mm(in)



Tooling Parts Detail


ITEM			10 Position		12 Position : Opt.	
			mm Unit	inch Unit	mm Unit	inch Unit
Turning Holder	O.D Clamper		5	5	5	5
	O.D Holder	Extension	Opt.	Opt.	1	1
	Facing Holder		1	1	1	1
Boring Holder	I.D Holder	Single	4	4	5	5
	U-Drill	Cap	1	1	1	1
Driven Holder	Straight Mill Holder	Standard	-	-	-	-
		TTC	-	-	-	-
	Angular Mill Holder	Standard	-	-	-	-
		TTC	-	-	-	-
Socket	Boring	Ø12 (Ø1/2")	1	1	1	1
		Ø16 (Ø5/8")	1	1	1	1
		Ø20 (Ø3/4")	1	1	1	1
		Ø25 (Ø1")	1	1	1	1
		Ø32 (Ø1 1/4")	1	1	1	1
		Ø40 (Ø1 1/2")	1	1	1	1
	Drill	MT 1 x MT 2	Opt.	Opt.	Opt.	Opt.
		MT 2	Opt.	Opt.	Opt.	Opt.
		MT 3	Opt.	Opt.	Opt.	Opt.
		MT 4	Opt.	Opt.	Opt.	Opt.
	ER Collet		-	-	-	-

Specifications are subject to change without notice for improvement.

SPECIFICATIONS

Tooling System (SE2600M/LM | SE2600Y/LY)

unit : mm(in)




Tooling Parts Detail

ITEM			12 Position		24 Position : Opt.	
			mm Unit	inch Unit	mm Unit	inch Unit
Turning Holder	O.D Holder	Right/Left	4	4	3	3
		Double	-	-	1	1
	Facing Holder		1	1	1	1
	Cutting Holder		-	-	-	-
Boring Holder	I.D Holder	Single	3	3	2	2
		Double	-	-	-	-
		Triple	-	-	1	1
	U-Drill Holder	Cap	1	1	1	1
Driven Holder	Straight Mill Holder	Standard	2	2	2	2
	Angular Mill Holder	Standard	2	2	2	2
Socket	Boring	Ø10 (Ø3/8")	1	1	1	1
		Ø12 (Ø1/2")	1	1	1	1
		Ø16 (Ø5/8")	1	1	1	1
		Ø20 (Ø3/4")	1	1	1	1
		Ø25 (Ø1")	1	1	1	1
		Ø32 (Ø1 1/4")	1	1	1	1
	Drill	MT 1	Opt.	Opt.	Opt.	Opt.
		MT 2	Opt.	Opt.	Opt.	Opt.
		MT 3	Opt.	Opt.	Opt.	Opt.
	ER Collet		1 Set	1 Set	1 Set	1 Set
	Adapter Set		Opt.	Opt.	Opt.	Opt.

SPECIFICATIONS

Tooling System (SE2600SY/LSY)

unit : mm(in)



Tooling Parts Detail

ITEM			12 Position		24 Position : Opt.	
			mm Unit	inch Unit	mm Unit	inch Unit
Turning Holder	O.D Holder	Right/Left	2	2	1	1
		Double (Main & Sub)	1	1	-	-
		Double (Main)	-	-	1	1
		Double (Sub)	-	-	1	1
	Facing Holder		1	1	1	1
Boring Holder	I.D Holder	Single	2	2	2	2
		Double	1	1	-	-
		Triple	-	-	1	1
		Cap	1	1	1	1
	U-Drill Holder		1	1	1	1
Driven Holder	Straight Mill Holder	Standard	2	2	2	2
	Angular Mill Holder	Standard	2	2	2	2
Socket	Main Spindle Boring	Ø10 (Ø3/8")	1	1	1	1
		Ø12 (Ø1/2")	1	1	1	1
		Ø16 (Ø5/8")	1	1	1	1
		Ø20 (Ø3/4")	1	1	1	1
		Ø25 (Ø1")	1	1	1	1
		Ø32 (Ø1 1/4")	1	1	1	1
	Sub Spindle Boring	Ø8 (5/16")	1	1	1	1
		Ø12 (1/2")	1	1	1	1
		Ø16 (5/8")	1	1	1	1
	Drill	MT 1	Opt.	Opt.	Opt.	Opt.
		MT 2	Opt.	Opt.	Opt.	Opt.
		MT 3	Opt.	Opt.	Opt.	Opt.
	ER Collet		1 Set	1 Set	1 Set	1 Set
	Adapter Set		Opt.	Opt.	Opt.	Opt.

Specifications are subject to change without notice for improvement.

unit : mm(in)

O.D Tool Holder

796 (31.3) SP. Nose O.D Holder

680 (26.8) Z-St.

671 (26.4) Max turning length

90 (3.5), 100 (3.9), 330 (13.0)

7 (0.3), 161.5 (6.4), 156 (6.1), 109 (4.3)

109 (4.3), 9 (0.4), 200 (7.9), 35 (1.4)

50 (2), 18 (0.7), 100 (3.9), 43 (1.7), 96 (3.8), 110 (4.3), 8 (0.3)

285 (10.4) X-St., 235 (9.3), 30 (1.2)

470 (18.5)

700 (27.6) T/S-St.

20 (0.8), 40 (1.6)

957 (37.7)

Ø220 (Ø8.7), Ø254 (Ø10")

36.1 (1.4), 102.9 (4.1)

8 (0.3)

I.D Tool Holder

796 (31.3) SP. Nose O.D. Holder
 680 (26.8) Z-St.
 678 (26.7) Max turning length

116 (4.6)
 18 (0.7)
 100 (3.9)
 43 (1.7)
 96 (3.8)
 110 (4.3)
 8 (0.3)
 230
 285 (10.4) X-St.
 35
 700 (27.6) T/S-St.
 36.1 (1.4)
 102.9 (4.1)

Ø220 (Ø8.7)
 Ø254 (Ø10")
 Ø150 (Ø5.9)
 Ø122 (Ø4.8)
 90 (3.5)
 100 (3.9)
 200 (7.9)
 161.5 (6.4)
 156 (6.1)
 109 (4.3)
 470 (18.5)
 8 (0.3)
 105 (4.1)
 40 (1.6)

957 (37.7)

SE2600 Series
CNC Turning Center

unit : mm(in)

[illegible]

I.D. Tool Holder

1216 (SP NOSE-OD HOLDER)

1100 (Z-St.)

1098 (Max turning length)

90 100 3390

200 161.5 156 109

470

50 18 116 2

100 43 158.2

110

265 (X-St.) 230 35

Ø220 Ø254 (10")

76.3 124.9

1100 (T/S-St.)

120 (QUILL ST)

105 40 124.9

1419.2


Ø50

SPECIFICATIONS


Tooling Travel Range (SE2600M)

unit : mm(in)


O.D Tool Holder



I.D Tool Holder



Face Tool Holder



SE2600 Series
CNC Turning Center

unit : mm(in)

Straight Mill Holder

781 (30.7) SP. Nose O.D. Holder
680 (26.8) Z-St.

90 (3.5)
130 (5.1)
527 (20.7)

165 (6.5)
156 (6.1)
109 (4.3)

45 (1.8)
60 (2.4)

118 (4.6)
28 (1.1)
15 (0.6)
18 (0.7)
100 (3.9)
43 (1.7)
96 (3.8)
110 (4.3)
110 (4.3)

50 (2)

Ø220 (Ø8.7)
Ø254 (Ø10")

8 (0.3)

255 (10) X-St
245 (9.6)
10 (0.4)

220 (8.7)
35 (1.4)
25 (1)

700 (27.6) T/S-St.
957 (37.7)

36.1 (1.4)
102.9 (4.1)
8 (0.3)

470 (18.5)

Angular Mill Holder

781 (30.7) SP. Nose O.D. Holder
680 (26.8) Z-St.
621 (24.4)

90 (3.5)
130 (5.1)
527 (20.7)

59 (2.3)
59 (2.3)
42 (1.6)
85 (3.3)
165 (6.5)
156 (6.1)
109 (4.3)

50 (2)
18 (0.7)
100 (3.9)
43 (1.7)
96 (3.8)
110 (4.3)
8 (0.3)
255 (10) X-St.
220 (8.7)
35 (1.4)
115 (4.5)
140 (5.5)
87 (3.4)
50 (2)
92


700 (27.6) T/S-St.
957 (37.7)

Ø220 (Ø8.7)
Ø254 (Ø10")
36.1 (1.4)
102.9 (4.1)

470 (18.5)

8 (0.3)

unit : mm(in)



SE2600 Series
CNC Turning Center

unit : mm(in)

Straight Mill Holder


Angular Mill Holder

SPECIFICATIONS


Tooling Travel Range (SE2600Y)

unit : mm(in)


O.D Tool Holder



I.D Tool Holder



Face Tool Holder




SPECIFICATIONS


Tooling Travel Range (SE2600Y)

unit : mm(in)

Straight Mill Holder






Angular Mill Holder



Tooling Travel Range (SE2600LY)

unit : mm(in)






SE2600 Series
CNC Turning Center

unit : mm(in)

[illegible]

Angular Mill Holder

Tooling Travel Range (SE2600SY)




SPECIFICATIONS


Tooling Travel Range (SE2600SY)

unit : mm(in)


Straight Mill Holder



Angular Mill Holder



Sub Angular Mill Holder




SPECIFICATIONS


Tooling Travel Range (SE2600LSY)

unit : mm(in)


O.D Tool Holder



I.D Tool Holder



Face Tool Holder



SE2600 Series
CNC Turning Center

unit : mm(in)

Straight Mill Holder

Angular Mill Holder

Angular Mill Holder

Dimensions (mm / inches):

- Overall Length:** 1369.5 (53.9) SP NOSE-SP NOSE
- Overall Width:** 470 (18.5)
- Spindle Interface:**
 - Ø220 (Ø8.7)
 - 50 (1)
 - 82 (3.2)
 - 36 (1.4)
 - 18 (0.7)
 - 100 (3.9)
 - 43 (1.7)
 - 110 (4.3)
- Holder Body:**
 - 255 (10) X-St.
 - 220 (8.7)
 - 35 (1.4)
 - 35 (1.4)
 - 130 (5.1)
 - 80 (3.5)
 - 125 (4.9)
 - 88 (3.5)
- Spindle Nose-Flange:**
 - 2.2 (0.9)
 - SP NOSE-FLANGE
 - Ø175 (6")
 - 81 (3.2)
 - 10 (0.4)
 - 32.5 (1.3)
- Top View Dimensions:**
 - 90 (3.5)
 - 140 (5.5)
 - 218 (8.6)
 - 289 (11.4)
 - 165 (6.5)
 - 155.5 (6.2)
 - 99 (3.9)
 - 57 (2.2)
 - 85 (3.3)
 - 119 (4.7)
 - 87 (3.4)
 - 50 (2)

Sub Angular Mill Holder

SPECIFICATIONS

Specifications

[] : Option

MODEL			SE2600	SE2600L
CAPACITY	Swing Over the Bed	mm(in)	Ø600 (Ø23.6")	
	Swing Over the Carriage	mm(in)	Ø460 (18.1")	
	Max. Turning Dia.	mm(in)	Ø460 (18.1")	
	Max. Turning Length	mm(in)	671 (26.4")	1,091 (43")
	Bar Capacity	mm(in)	Ø81 (3.2")	
SPINDLE	Chuck Size	inch	10"	
	Spindle Bore	mm(in)	Ø91 (3.6")	
	Spindle Speed (rpm)	r/min	3,500 [2,500]	
	Motor (Max/Cont.)	kW(HP)	18.5/11 (25/15) [26/18.5 (35/25)]	
	Torque (Max/Cont.)	N·m (lb·ft)	470.9/286.4 (347.3/211.2) [734/522 (541.4/385)]	
	Spindle Type	-	BELT	
	Spindle Nose	-	A2-8	
	C-axis Indexing	deg	0.001°	
FEED	Travel (X/Z)	mm(in)	265/680 (10.1"/26.8")	265/1,100 (10.1"/43.3")
	Rapid Traverse Rate (X/Z)	m/min (ipm)	30/30 (1,181/1,181)	
	Slide Type	-	ROLLER LM GUIDE	
TURRET	No. of Tools	ea	10 [12]	
	Tool Size	OD mm(in)	□25 (□1")	
		ID mm(in)	Ø50 (Ø2")	
	Indexing Time	sec	0.15	
LIVE TOOL	Motor (Max/Cont.)	kW(HP)	-	
	Milling Tool Speed (rpm)	r/min	-	
	Torque (Max/Cont.)	N·m (lb·ft)	-	
	Collet Size	mm(in)	-	
	Type	-	-	
TAIL STOCK	Taper	-	MT#4	
	Quill Dia.	mm(in)	-	Ø80 (Ø3.1")
	Quill Travel	mm(in)	-	120 (4.7")
	Travel	mm(in)	700 (27.6")	1,100 (43.3")
TANK CAPACITY	Coolant Tank	ℓ (gal)	200 (52.8)	230 (60.8)
	Lubricating Tank	ℓ (gal)	0.7 (0.18)	1.8 (0.48)
POWER SUPPLY	Electric Power Supply	kVA	18	
	Thickness of Power Cable	mm ²	Over 16	
	Voltage	V/Hz	220/60 (200/50*)	
MACHINE	Floor Space (L×W)	mm(in)	3,255×1,900 (128.1"×74.8")	3,715×2,000 (146.3"×78.7")
	Height	mm(in)	1,730 (68.1")	
	Weight	kg(lb)	4,200 (9,259)	5,000 (11,023)
NC	Controller	-	FANUC i Series - Smart Plus	

Specifications are subject to change without notice for improvement.

SPECIFICATIONS

Specifications

[] : Option

MODEL			SE2600M		SE2600LM	
CAPACITY	Swing Over the Bed		mm(in)	Ø600 (Ø23.6")		
	Swing Over the Carriage		mm(in)	Ø460 (18.1")		
	Max. Turning Dia.		mm(in)	Ø380 (15")		
	Max. Turning Length		mm(in)	630 (24.8")		1,050 (41.3")
	Bar Capacity		mm(in)	Ø81 (3.2")		
SPINDLE	Chuck Size		inch	10"		
	Spindle Bore		mm(in)	Ø91 (3.6")		
	Spindle Speed (rpm)		r/min	3,500 [2,500]		
	Motor (Max/Cont.)		kW(HP)	18.5/11 (25/15) [26/18.5 (35/25)]		
	Torque (Max/Cont.)		N·m (lb·ft)	470.9/286.4 (347.3/211.2) [734/522 (541.4/385)]		
	Spindle Type		-	BELT		
	Spindle Nose		-	A2-8		
	C-axis Indexing		deg	0.001°		
FEED	Travel (X/Z)		mm(in)	255/680 (10"/26.8")		255/1,100 (10"/43.3")
	Rapid Traverse Rate (X/Z)		m/min (ipm)	30/30 (1,181/1,181)		
	Slide Type		-	ROLLER LM GUIDE		
TURRET	No. of Tools		ea	12 [24]		
	Tool Size	OD	mm(in)	□25 (□1") [24T : □20 (□3/4")]		
		ID	mm(in)	SINGLE Ø40 (Ø1 1/2"), DOUBLE Ø20 (Ø3/4") [24T : SINGLE Ø40 (Ø1 1/2"), TRIPLE : Ø20 (Ø3/4")]		
	Indexing Time		sec	0.15		
	LIVE TOOL	Motor (Max/Cont.)		kW(HP)	5.5/3.7 (7.4/5)	
Milling Tool Speed (rpm)		r/min	6,000			
Torque (Max/Cont.)		N·m (lb·ft)	52.5/26.5 (38.7/19.5)			
Collet Size		mm(in)	Ø16 (Ø5/8") : ER25			
Type		-	BMT55			
TAIL STOCK	Taper		-	MT#4		
	Quill Dia.		mm(in)	-		Ø80 (Ø3.1")
	Quill Travel		mm(in)	-		120 (4.7")
	Travel		mm(in)	700 (27.6")		1,100 (43.3")
TANK CAPACITY	Coolant Tank		ℓ (gal)	200 (52.8)		230 (60.8)
	Lubricating Tank		ℓ (gal)	0.7 (0.18)		1.8 (0.48)
POWER SUPPLY	Electric Power Supply		kVA	18		
	Thickness of Power Cable		mm²	Over 16		
	Voltage		V/Hz	220/60 (200/50*)		
MACHINE	Floor Space (L×W)		mm(in)	3,255×1,900 (128.1"×74.8")		3,715×2,000 (146.3"×78.7")
	Height		mm(in)	1,730 (68.1")		
	Weight		kg(lb)	4,300 (9,480)		5,100 (11,244)
NC	Controller		-	FANUC i Series - Smart Plus		

Specifications are subject to change without notice for improvement.

SE2600 Series
CNC Turning Center

44
+
45

SPECIFICATIONS

Specifications

[] : Option

MODEL			SE2600Y		SE2600LY	
CAPACITY	Swing Over the Bed	mm(in)	Ø630 (Ø24.8")			
	Swing Over the Carriage	mm(in)	Ø630 (Ø24.8")			
	Max. Turning Dia.	mm(in)	Ø380 (15")			
	Max. Turning Length	mm(in)	653 (25.7")		1,073 (42.2")	
	Bar Capacity	mm(in)	Ø81 (Ø3.2")			
SPINDLE	Chuck Size	inch	10"			
	Spindle Bore	mm(in)	Ø91 (Ø3.6")			
	Spindle Speed (rpm)	r/min	3,500 [2,500]			
	Motor (Max/Cont.)	kW(HP)	18.5/11 (25/15) [26/18.5 (35/25)]			
	Torque (Max/Cont.)	N·m (lb·ft)	470.9/286.4 (347.3/211.2)[734/522 (541.4/385)]			
	Spindle Type	-	BELT			
	Spindle Nose	-	A2-8			
	C-axis Indexing	deg	0.001°			
FEED	Travel (X/Y/Z)	mm(in)	255/110{±55}/680 (10"/4.3"/26.8")		255/110{±55}/1,100 (10"/4.3"/43.3")	
	Rapid Traverse Rate (X/Y/Z)	m/min (ipm)	30/10/30 (1,181/394/1,181)		30/10/30/15 (1,181/394/1,181/591)	
	Slide Type	-	ROLLER LM GUIDE			
TURRET	No. of Tools		ea	12 [24]		
	Tool Size	OD	mm(in)	□25 (□1 ") [24T : □20 (□3/4")]		
		ID	mm(in)	SINGLE Ø40 (Ø1 1/2"), DOUBLE Ø20 (Ø3/4") [24T : SINGLE Ø40 (Ø1 1/2"), TRIPLE : Ø20 (Ø3/4")]		
	Indexing Time		sec	0.15		
	LIVE TOOL	Motor (Max/Cont.)	kW(HP)	5.5/3.7 (7.4/5)		
Milling Tool Speed (rpm)		r/min	6,000			
Torque (Max/Cont.)		N·m (lb·ft)	52.5/26.5 (38.7/19.5)			
Collet Size		mm(in)	Ø16 (Ø5/8") : ER25			
Type		-	BMT55			
TAIL STOCK	Taper	-	MT#4			
	Quill Dia.	mm(in)	-		Ø80 (Ø3.1 ")	
	Quill Travel	mm(in)	-		120 (4.7")	
	Travel	mm(in)	700 (27.6")		1,100 (43.3")	
TANK CAPACITY	Coolant Tank	ℓ (gal)	200 (52.8)		230 (60.8)	
	Lubricating Tank	ℓ (gal)	0.7 (0.18)		1.8 (0.48)	
POWER SUPPLY	Electric Power Supply	kVA	22			
	Thickness of Power Cable	mm²	Over 16			
	Voltage	V/Hz	220/60 (200/50*)			
MACHINE	Floor Space (L×W)	mm(in)	3,345×2,000 (131.7"×78.7")		3,805×2,100 (149.8"×82.7")	
	Height	mm(in)	1,960 (77.2")			
	Weight	kg(lb)	4,800 (10,582)		5,600 (12,346)	
NC	Controller	-	FANUC i Series - Smart Plus			

Specifications are subject to change without notice for improvement.

SPECIFICATIONS

Specifications

[] : Option

MODEL			SE2600SY	SE2600LSY
CAPACITY	Swing Over the Bed	mm(in)	Ø630 (Ø24.8")	
	Swing Over the Carriage	mm(in)	Ø630 (Ø24.8")	
	Max. Turning Dia.	mm(in)	Ø380 (15")	
	Max. Turning Length	mm(in)	653 (25.7")	1,073 (42.2")
	Bar Capacity	mm(in)	Main : Ø81 (Ø3.2") Sub : Ø51 (Ø2")	
SPINDLE	Chuck Size	inch	Main : 10" Sub : 6"	
	Spindle Bore	mm(in)	Main : Ø91 (Ø3.6") Sub : Ø60 (Ø2.4")	
	Spindle Speed (rpm)	r/min	Main : 3,500 [2,500] Sub : 4,500	
	Motor (Max/Cont.)	kW(HP)	Main : 18.5/11 (25/15) [26/18.5 (35/25)] Sub : 7.5/5.5 (10/7.5)	
	Torque (Max/Cont.)	N·m (lb·ft)	Main : 470.9/286.4 (347.3/211.2) [734/522 (541.4/385)] Sub : 85/47 (62.7/34.7)	
	Spindle Type	-	BELT	
	Spindle Nose	-	Main : A2-8 Sub : A2-5	
	C-axis Indexing	deg	0.001°	
FEED	Travel (X/Y/Z/ZB)	mm(in)	255/110 (±55)/680/660 (10"/4.3"/26.8"/26")	255/110 (±55)/1,100/1,080 (10"/4.3"/43.3"/42.5")
	Rapid Traverse Rate (X/Y/Z/ZB)	m/min (ipm)	30/10/30/15 (1,181/394/1,181/591)	
	Slide Type	-	ROLLER LM GUIDE	
TURRET	No. of Tools	ea	12 [24]	
	Tool Size	OD	mm(in)	
		ID	mm(in)	
	Indexing Time	sec	0.15	
LIVE TOOL	Motor (Max/Cont.)	kW(HP)	5.5/3.7 (7.4/5)	
	Milling Tool Speed (rpm)	r/min	6,000	
	Torque (Max/Cont.)	N·m (lb·ft)	52.5/26.5 (38.7/19.5)	
	Collet Size	mm(in)	Ø16 (Ø5/8") : ER25	
	Type	-	BMT55	
TAIL STOCK	Taper	-	-	
	Quill Dia.	mm(in)	-	
	Travel	mm(in)	-	
TANK CAPACITY	Coolant Tank	ℓ (gal)	200 (52.8)	230 (60.8)
	Lubricating Tank	ℓ (gal)	0.7 (0.18)	
POWER SUPPLY	Electric Power Supply	kVA	22	28
	Thickness of Power Cable	mm ²	Over 16	Over 25
	Voltage	V/Hz	220/60 (200/50*)	
MACHINE	Floor Space (L×W)	mm(in)	3,345×2,000 (131.7"×78.7")	3,805×2,100 (149.8"×82.7")
	Height	mm(in)	1,960 (77.2")	
	Weight	kg(lb)	5,000 (11,023)	5,800 (12,787)
NC	Controller	-	FANUC i Series - Smart Plus	

Specifications are subject to change without notice for improvement.

CONTROLLER

FANUC i Series - Smart Plus

[] : Option


Controlled axis / Display / Accuracy Compensation	
Control axis	2 axis (X, Z) / 3 axis (X, Z, C) / 4 axis (X, Z, Y, C) 5 axis (X, Z, B, C, A) / 6 axis (X, Z, Y, B, C, A) 7 axis (X1/Z1, X2/Z2, B2, C1/C2)
Simultaneously controlled axis	2 axis [Max. 4 axis]
Designation of spindle axis	3 axis [Max. 4 axis]
Least setting Unit	X, Z, Y, B axis : 0.001 mm (0.0001 inch) C, A axis : 0.001 deg
Least input increment	X, Z, Y, B axis : 0.001 mm (0.0001 inch) C, A axis : 0.001 deg
Inch / Metric conversion	G20 / G21
High response vector control	
Interlock	All axis / Each axis
Machine lock	All axis
Backlash compensation	± 0~9999 pulses (exc.Rapid traverse / Cutting feed)
Position switch	
LCD / MDI	15 inch LCD unit (with Touch Panel)
Feedback	Absolute motor feedback
Stored stroke check 1	Over travel
Stored stroke check 2, 3	
PMC axis control	
Operation	
Automatic operation (Memory)	
MDI operation	
DNC operation	Needed DNC software / CF card
Program restart	
Wrong operation prevention	
Program check function	Dry run
Single block	
Search function	Program Number / Sequence Number
Interpolation functions	
Nano interpolation	
Positioning	G00
Linear interpolation	G01
Circular interpolation	G02, G03
Exact stop mode	Single : G09, Continuous : G61
Dwell	G04, 0 ~ 9999.9999 sec
Skip	G31
Reference position return	1st reference : G28, 2nd reference : G30 Ref. position check : G27
Thread synchronous cutting	G33
Thread cutting retract	
Variable lead thread cutting	
Multi / Continuous threading	
Feed function / Acc. & Dec. control	
Manual feed	Rapid traverse Jog : 0~2,000 mm/min (79 ipm) Manual handle : x1, x10, x100 pulses Reference position return
Cutting Feed command	Direct input F code
Feedrate override	0 ~ 200% (10% Unit)
Rapid traverse override	1%, F25%, 50%, 100%
Override cancel	
Feed per minute	G98
Feed per revolution	G99
Look-ahead block	1 block
Program input	
Tape Code	EIA / ISO
Optional block skip	9 ea
Program stop / end	M00, M01 / M02, M30
Maximum command unit	± 999,999.999 mm (± 99,999.9999 inch)
Plane selection	X-Y : G17 / Z-X : G18 / Y-Z : G19
Workpiece coordinate system	G52, G53, 6 pairs (G54 ~ G59)
Manual absolute	Fixed ON
Programmable data input	G10
Sub program call	10 folds nested
Custom macro	#100 ~ #199, #500 ~ #999
G code system	A, B/C
Programmable mirror image	G51.1, G50.1
G code preventing buffering	G4.1
Direct drawing dimension program	Including Chamfering / Corner R
Conversational Program	SmartGuide-i

Program input	
Multiple repetitive cycles I, II	
Canned cycle for turning	
Auxiliary function / Spindle speed function	
Auxiliary function	M & 4 digit
Level-up M Code	High speed / Multi / Bypass M code
Spindle speed function	S & 5 digit, Binary output
Spindle override	0% ~ 150% (10% Unit)
Multi position spindle orientation	M19 (S##)
Rigid tapping	
Constant surface speed control	G96, G97
Tool function / Tool compensation	
Tool function	T & 2 digit + Offset 2 digit
Tool life management	
Tool offset pairs	128 pairs
Tool nose radius compensation	G40, G41, G42
Geometry / Wear compensation	
Direct input of offset measured B	
Editing function	
Part program storage size	5,120m (2MB)
No. of registerable programs	1,000 ea
Program protect	
Background editing	
Extended part program editing	Copy, move and change of NC program
Memory card program edit	
Data input / output & Interface	
I/O interface	CF card, USB memory Embedded Ethernet interface
Screen hard copy	
External message	
External key input	
External workpiece number search	
Automatic data backup	
Setting, display and diagnosis	
Self-diagnosis function	
History display & Operation	Alarm & Operator message & Operation
Run hour / Parts count display	
Maintenance information	
Actual cutting feedrate display	
Display of spindle speed / T code	
Graphic display	
Operating monitor screen	Spindle / Servo load etc.
Power consumption monitoring	Spindle & Servo
Spindle / Servo setting screen	
Multi language display	Support 24 languages
Display language switching	Selection of 5 optional Languages
LCD Screen Saver	Screen saver
Unexpected disturbance torque	BST (Back spin torque limit)
Function for machine type	
Cs contour control (C & A axis)	Mill, MS, Y, SY, LF-Mill, TTMS, TTSY
Polar coordinate interpolation	Mill, MS, Y, SY, LF-Mill, TTMS, TTSY
Cylindrical interpolation	Mill, MS, Y, SY, LF-Mill, TTMS, TTSY
Polygon turning (2 Spindles)	Mill, MS, Y, SY, LF-Mill, TTMS, TTSY
Canned cycle for drilling	Mill, MS, Y, SY, LF-Mill, TTMS, TTSY
Spindle orientation expansion	MS, SY TTS, TTMS, TTSY
Spindle synchronous control	MS, SY TTS, TTMS, TTSY
Torque control	MS, SY TTS, TTMS, TTSY
Y axis offset	Y, SY, TTSY
Arbitrary angular control	Y, SY, TTSY
Composite / Superimposed control	MS, SY, TTS, TTMS, TTSY
Balance cutting	TTS, TTMS, TTSY
Option	
Fast ethernet	Needed option board
Data server	Needed option board
Protection of data at 8 levels	
Tool offset pairs	200 pairs
Helical interpolation	
Look-ahead Block	40 ea, 200 ea (AICC II)

Figures in inch are converted from metric values.

The FANUC controller specifications are subject to change based on the policy of company CNC supplying.

GLOBAL NETWORK



WIA MACHINE TOOLS

Headquarter / R&D Center 106, Yongji-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Republic of Korea TEL : +82 55 225 9999

Overseas Sales Team 13, Iljik-ro 12beon-gil, Gwangmyeong-si, Gyeonggi-do, Republic of Korea TEL : +82 55 225 9645

OVERSEAS OFFICES

America corp. 450 Commerce Blvd, Carlstadt, NJ 07072, USA TEL : +1-201-987-7298

Europe GmbH Alexander-Fleming-Ring 57, 65428 Russelsheim Germany TEL : +49-0-6142-9256-0

China Company No.16 Fenghuang Road, Fenghuang Town, Zhangjiagang City, Jiangsu Province, China TEL : +86-21-6427-9885

CIS Branch Office 050051, Kazakhstan, Almaty, Elebekova street 10, B.3 Office no. 103 TEL : +7-727-355-7133

India Branch Office #4/169, 1st Floor, LOTTE BLDG, Rajiv Gandhi Salai, (OMR), Kandanchavadi, Chennai - 600096, Tamilnadu, India TEL : +91-76-0490-3348

WIN MACHINE TOOLS



home page



facebook



youtube



instagram



linkedin